

TECHNICAL SPECIFICATION

Stork Pipe Repair

Stork fabricate, supply and install under pressure tees, pipe repair clamps, flange adaptors, universal coupling and studded flange converters to your specification.

Steel Pipe Repair Clamps :

- For use on ductile iron, cast iron, PVC, asbestos cement, steel, GRP and HDPE pipes
- Can be used up to 16bar on water pipes and 2bar on gas compressed air pipes

Under Pressure Tees - Branch Saddles:

- Hot tap and line stop tees for metallic and plastic pipe
- All welded construction and heavy gauge stainless steel for high pressure branch connections
- Pressure ratings to your requirements from 0.5bar to 20bar working pressure, 30bar test pressure
- UPTs can be manufactured for all pipe types including ductile iron, cast iron, PE, PVC, steel and AC
- Diameters : 90mm to 2000mm
- UPT Lengths: Min 250mm Max 3000mm
- UPT types: Single and split collar
- Temp Range: -40°C to 200°C

Mini/Snap Clamps:

- For the repair of holes in water pipes
- 16bar rated
- Temperature up to 90°C
- EPDM gaskets
- Stainless shells and steel lugs and bolt
- 316 Stainless Steel available on request
- Silicone and viton for high temperatures
- ½" up to 2 meters diameter

Bossed Pipe Service Saddles:

Female or male threaded outlets, popular sizes are stock items and we can also manufacture to your specific requirements. Heavy gauge stainless steel is vulcanized into the gasket at the time of moulding, to ensure that it:

- Fits permanently
- Fits perfectly
- Provides a smooth transition from gasket to metal

Committed to technical innovation:

